

A  
C  
E  
I  
N  
S  
U  
L  
A  
T  
I  
O  
N  
A  
D  
H  
E  
S  
I  
V  
E

# INSULATION ADHESIVE (INA)

## High Strength Contact Cement

**ACE INSULATION ADHESIVE (INA)** is a high strength, solvent-based contact cement suitable for use in bonding pipe insulation tubes and sheets and most other clean, dry surfaces. **ACE INSULATION ADHESIVE (INA)** dries flexibly to form a positive vapor barrier to aid in the prevention of pipe sweat.

**FEATURES & BENEFITS**

- Solvent- based formula – dries quickly.
- High strength bond – provides permanent seal.

**DIRECTIONS for USE:** Clean and dry surface prior to application. Shake can before used. Brush **ACE INSULATION ADHESIVE (INA)** onto both surfaces to be bonded. Allow surfaces to dry to touch but remain tacky under pressure. Bond surfaces together.

**SAFETY:** In the event of skin contact, IMMEDIATELY flush area with soap and water. For eye contact, flush eyes with clean water for at least 15 minutes. Seek IMMEDIATE medical attention if irritation persists. If ingested, do NOT induce vomiting, seek IMMEDIATE medical attention.

**CAUTION:** Contains Toulene, Hexane and Acetone. Extremely flammable mixture. Vapors may ignite explosively. Use only with cross-ventilation. Keep mixture away from heat, sparks or open flame. Extinguish all flames, pilot lights, electrical motors, etc. until all vapors are gone. Close container after use. Avoid breathing mists or vapors. Use with adequate ventilation. Do not ingest. **KEEP OUT OF THE REACH OF CHILDREN.**

**PHYSICAL PROPERTIES**

APPEARANCE	.....	Liquid
COLOR	.....	Clear
pH	.....	NA
SPECIFIC GRAVITY	.....	0.88
PACKAGING	.....	24x1/2 pint/case 12x1 pint/case 12x1 quart/case