ACCESSORIES: PLASTIC SOLENOID VALVE, ZONE SENTRY VALVE

Electric Globe (Light Commercial)

Applications

The debris-tolerant operation of the 205 Series valves makes them an excellent choice for both clean and dirty water applications.

Size 1" plastic models

Performance

- Flow range from 5-25 GPM
- Pressure range from 10-150 psi
- Manual external bleed
- Debris-tolerant design
- · High-flow, low friction loss design
- · Optional flow control allows precise flow adjustment and manual shutoff

Quality Construction

- Heavy-duty, corrosion and UV-resistant PVC construction
- Stainless steel and fabric-reinforced synthetic rubber diaphragm
- Encapsulated solenoid
- Available in NPT or slip configuration for high-volume applications
- Removable, tamper-resistant flow control handle
- Easily serviced without removal from the system
- 1 year limited warranty



Size	Part Number
SOLENOID VALVE	205TF

ELECTRICAL SPECIFICATIONS

- Solenoid: 24 VAC
- Inrush volt-amp: 24 VAC-11.50 VA
- Inrush current: .4 amp
- Holding volt-amp: 24 VAC-5.75 VA
- Holding current: .2 amp

Zone Sentry® Zone Valve Zone Valves with Multi-function LED

The Taco Zone Sentry® Zone Valves Zone Valves provide on-off, normally open or normally closed control in both open and closed hydronic systems. The valves can be used in a wide variety of heating and non condensing cooling applications, primarily designed for use with baseboard, fan coils, radiators, convectors, air handlers, heat pumps and radiant applications.

Features

- Uses up to 93% less energy than other commonly installed zone valves
- Up to 12 valves on (1) 40VA transformer
- · Multi function LED assists with troubleshooting
- Bidirectional flow (you can't install the valve backwards)
- · The actuator mounts on the valve in either direction
- · 125 PSI shut-off pressure with industry leading Cv's
- · Quick release actuator mounting clip
- · Manual override button
- · Positional indicator shows the ball valve's actual position



Size	Part Number
Zone Sentry Valve 1" NPT 2-Way 24V	Z100AAT2
Zone Sentry Valve 3/4" NPT 2-Way 24V	Z075T2-1
Geo-Sentry Geothermal Zone Valve 3/4" NPT 2-Way 24V	V075TG-1

Specifications available upon request



1-866-646-6724 712-652-3424 www.bdmfginc.com