

# PRODUCT INFORMATION PACKET



Model No: EM3729F  
Catalog No: EM3729F  
1/3 HP Condenser Fan Motor, 1075 RPM, 208-230 Volts, 48 Frame, TEAO  
Condenser Fans Motors



Regal and Century are trademarks of Regal Rexnord Corporation or one of its affiliated companies.  
©2021 Regal Rexnord Corporation, All Rights Reserved. MC017097E





### Nameplate Specifications

Output HP	1/3 Hp	Output KW	0.25 kW
Frequency	60 Hz	Voltage	208-230 V
Current	2.2-2.5 A	Speed	1075 rpm
Service Factor	1	Phase	1
Duty	Air Over	Insulation Class	F
Frame	48Y	Enclosure	Totally Enclosed
Thermal Protection	Automatic	Ambient Temperature	70 °C
UL	Recognized	CSA	Y
CE	N	Number of Speeds	1


### Technical Specifications

Electrical Type	Permanent Split Capacitor	Starting Method	Across The Line
Poles	6	Rotation	Reversible
Mounting	Extended Studs	Motor Orientation	Any
Drive End Bearing	Ball	Opp Drive End Bearing	Ball
Frame Material	Rolled Steel	Shaft Type	Flat
Overall Length	11.17 in	Frame Length	4.00 in
Shaft Diameter	0.500 in	Shaft Extension	6.0 in
Outline Drawing	EM3729F-S01	Connection Drawing	614131-292



This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:10/07/2021




REV	ECO	REV BY	DATE	APPD	DATE
B	ECO-0022458	jrupert	09-19-2011	jrupert	09-19-2011





- NOTES:
1. FOR USE WITH 614129 NAMEPLATE BLANK
  2. — — — — — INDICATES DIMENSION LIMITS
  3. DIE TO BE MADE FROM MASTER SUPPLIED BY A. O. SMITH CORPORATION
  4. DIE MUST PRODUCE A LEGIBLE IMPRESSION.

GEOMETRIC CHARACTERISTICS & SYMBOLS ∟ FLATNESS — STRAIGHTNESS ∠ ANGULARITY ⊥ PERPENDICULARITY (SQUARENESS) // PARALLELISM ○ ROUNDNESS (CIRCULARITY) ⊘ CYLINDRICITY △ PROFILE OF ANY SURFACE ⌒ PROFILE OF ANY LINE ↑ RUNOUT ⊕ TRUE POSITION ◎ CONCENTRICITY = SYMMETRY	UNLESS OTHERWISE SPECIFIED DIM. TOLERANCES ARE AS FOLLOWS: INCH X XX XXX XXXX mm ±.1 ±.02 ±.005 ±.0005 mm ±0.5 ±0.13 ±0.013 ANG. ±.50 DEG REMOVE BURRS & BREAK SHARP EDGES: INCH .003-.015 mm 0.1-0.4 CORNER FILLETS TO: INCH .020 mm 0.5 MACHINE SURFACES: INCH 125 mm 3.2 METRIC DIMS. SHOWN IN [BRACKETS]	DR BY: jrupert	09-19-2011	<div> <b>ELECTRICAL PRODUCTS COMPANY</b> <small>INNOVATION HAS A NAME. A DIVISION OF A. O. SMITH CORPORATION</small></div>		
		APPD: jrupert	09-19-2011			
		THIRD ANGLE PROJECTION 	EDS DATE 02-22-2008	DESCRIPTION CONN DIAGRAM NAMEPLATE		
			FORMAT REV F			
		CONFIDENTIAL: THIS DRAWING AND ITS INFORMATION ARE THE EXCLUSIVE AND CONFIDENTIAL PROPERTY OF A.O. SMITH CORP. AND ARE NOT TO BE DISCLOSED, DUPLICATED, DISTRIBUTED OR OTHERWISE USED WITHOUT THE WRITTEN CONSENT OF A.O. SMITH CORP. -ALL RIGHTS RESERVED. ASME Y14.5M 1994		SIZE A	DWG NO 614131-292	
				SCALE NONE	SHEET 1	


REVISION:	ECO	REVISADO POR:	FECHA:	APROBADO POR:	FECHA:
B	ECO-0022458	jrupert	09-19-2011	jrupert	09-19-2011



- NOTES:
1. FOR USE WITH 614129 NAMEPLATE BLANK
  2. — — — — — INDICATES DIMENSION LIMITS
  3. DIE TO BE MADE FROM MASTER SUPPLIED BY A. O. SMITH CORPORATION
  4. DIE MUST PRODUCE A LEGIBLE IMPRESSION.

CARACTERISTICAS DE GEOMETRIA Y SIMBOLOS ∇ PLANICIDAD — RECTITUD ∠ ANGULARIDAD ⊥ PERPENDICULARIDAD (A ESCUADRA) // PARALELISMO ○ REDONDEZ (CIRCULARIDAD) ⊘ CILINDRICIDAD ⌒ PERFIL DE CUALQUIER SUPERFICIE ⌒ PERFIL DE CUALQUIER LINEA ↑ VARIACION ⊕ POSICION REAL ◎ CONCENTRICIDAD ≡ SIMETRIA	A MENOS QUE SE ESPECIFIQUE DE OTRA MANERA, LAS TOLERANCIAS DE LAS DIMS. SON LAS SIGUIENTES: X XX XXX XXXX PULG ±.1 ±.02 ±.005 ±.0005 mm ±0.5 ±0.13 ±0.013 ANG. ±.50 GRADOS ELIMINAR REBABAS Y ORILLAS FILOSAS DEL BORDE. PULG .003-.015 mm 0.1-0.4 FILETEAR ESQUINA: PULG .020 mm 0.5 MAQUINAR SUPERFICIES PULG 125 mm 3.2 DIMS METRICAS MOSTRADAS [PARENTESIS]	DIBUJADO POR: jrupert	09-19-2011	<div><b>ELECTRICAL PRODUCTS COMPANY</b> Innovation has a name. <small>A DIVISION OF A. O. SMITH CORPORATION</small></div>			
		APROBADO POR: jrupert	09-19-2011	DESCRIPCION: CONN DIAGRAM NAMEPLATE			
		TERCER ANGULO DE PROYECCION					FECHA EDS: 02-22-2008 REV. FORMATO: F
		CONFIDENCIAL: ESTE DIBUJO Y SU INFORMACION SON PROPIEDAD DE USO EXCLUSIVO Y CONFIDENCIAL DE A.O.SMITH CORP. Y NO DEBERAN SER REVELADOS, DUPLICADOS, DISTRIBUIDOS O USARSE DE OTRA MANERA SIN EL CONSENTIMIENTO ESCRITO DE A.O. SMITH CORP. -TODOS LOS DERECHOS RESERVADOS.ASME Y14.5M 1994			TAMAÑO: A	NUMERO DE DIBUJO: 614131-292	
					ESCALA:NONE		HOJA: 1

版本	ECO	编制	日期	批准	日期
B	ECO-0022458	jrupert	09-19-2011	jrupert	09-19-2011



- NOTES:
1. FOR USE WITH 614129 NAMEPLATE BLANK
  2. — — — — — INDICATES DIMENSION LIMITS
  3. DIE TO BE MADE FROM MASTER SUPPLIED BY A. O. SMITH CORPORATION
  4. DIE MUST PRODUCE A LEGIBLE IMPRESSION.

形位公差 □ 平面度 — 直线度 ∠ 倾斜度 ⊥ 垂直度 // 平行度 ○ 圆度 ⊙ 圆柱度 △ 面轮廓度 ⌒ 线轮廓度 ↗ 圆跳动 ⊕ 位置度 ◎ 同轴度 ≡ 对称度	除另有注明 尺寸公差如下:  英寸 $\begin{matrix} X \\ \pm .1 \end{matrix}$ $\begin{matrix} XX \\ \pm .02 \end{matrix}$ $\begin{matrix} XXX \\ \pm .005 \end{matrix}$ $\begin{matrix} XXXX \\ \pm .0005 \end{matrix}$ 毫米 $\begin{matrix} \pm 0.5 \\ \pm 0.13 \end{matrix}$ $\begin{matrix} \pm 0.013 \end{matrix}$ 角度 $\pm .50$ 度 清理毛刺和尖棱 英寸 $\begin{matrix} .003-.015 \end{matrix}$ 毫米 $\begin{matrix} 0.1-0.4 \end{matrix}$ 内圆角 英寸 $\begin{matrix} .020 \end{matrix}$ 毫米 $\begin{matrix} 0.5 \end{matrix}$ 表面粗糙度 英制 $\begin{matrix} 125 \end{matrix}$ 米制 $\begin{matrix} 3.2 \end{matrix}$  米制尺寸显示在 [ ]	绘图:	jrupert	09-19-2011	<div><div><div>ACSmith</div><div>Innovation has a name.</div></div><div><div>ELECTRICAL PRODUCTS COMPANY</div><div>A DIVISION OF A. O. SMITH CORPORATION</div></div></div>					
		批准:	jrupert	09-19-2011	名称					
		第三角投影		图纸格式发布日期 02-22-2008	CONN DIAGRAM NAMEPLATE					
				图纸格式版本 F						
		机密：本图纸及相关信息所有权归A. O. SMITH公司所有。 未经A. O. SMITH公司书面授权，不得泄露、复制、传播或作 其他用途。一版权所有					图幅	A	图号	614131-292
		ASME Y14.5M 1994					比例	NONE		页号 1