

2' X 2' PLASTIC LAY-IN SUPPLY



3 CONE
HT-2X2-SPL
BOOT DIAMETER OPTIONS

6"	HT-2X2-SPL6
8"	HT-2X2-SPL8
10"	HT-2X2-SPL10
12"	HT-2X2-SPL12
14"	HT-2X2-SPL14



BORDERED
HT-2X2-BSPL
BOOT DIAMETER OPTIONS

6"	HT-2X2-BSPL6
8"	HT-2X2-BSPL8
10"	HT-2X2-BSPL10
12"	HT-2X2-BSPL12
14"	HT-2X2-BSPL14



PLAQUE
HT-2X2-PSPL
BOOT DIAMETER OPTIONS

6"	HT-2X2-PSPL6
8"	HT-2X2-PSPL8
10"	HT-2X2-PSPL10
12"	HT-2X2-PSPL12
BULLS EYE	HT-2X2-PSPLBE

• 2' X 2' Lay-In 3 Cone, Bordered, and Magnetic Plaque Diffuser Models • 3 Cone and Bordered both featuring an Easy Attach Knob • Magnetic Plaque featuring a Magnetic Engagement System (With Over 24 lbs. of Pull Force) • Standard White or Black Premix ABS (Additional Color Options Available) • Won't Rust, Corrode, Discolor, or Fade • Less conductive than metal (More resistant to "sweating") • Simple install and removal of diffuser for fast and efficient cleanability — Patent Pending



1. Easily attach to flex duct with cable tie/tape to pre-molded boot or boot added to Bulls Eye Back. Install Supply Back into drop ceiling grid without grille faces attached. Also available with Insulated Back option.
2. **3 CONE & BORDERED:** Insert Easy Attach Knob in grille face. Screw in center knob to connect to crossbar in boot. **MAGNETIC PLAQUE:** Line up four guide pins in grille face with four receptors in Supply Back. Magnetic Engagement System in Plaque stays in place with over 24 lbs of Pull Force.
3. Remove the 3 Cone and/or Bordered Diffuser by simply unscrewing Easy Attach Knob. Remove the Magnetic Plaque by pulling away from Supply Back. Grille face and Supply back can be cleaned with mild detergent. Test on inconspicuous spot to avoid discoloration.

