

# PC 745



## T-REX® PC 745 SUPER-TOUGH, PREMIUM, CO-EXTRUDED CLOTH TAPE

### TYPICAL APPLICATIONS

- For use on rough or dirty surfaces
- For heavy duty repairs that demand a ferociously strong hold
- Can also be used as a bottom board tape in the manufactured housing industry

### PRODUCT FEATURES

- Super-tough, premium co-extruded cloth tape
- Quick stick, even to rough or dirty surfaces
- Superior holding power
- Reinforced, waterproof backing

### CONSTRUCTION

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber adhesive

### STANDARD WIDTHS

1.88 in; 2.83 in

48 mm; 72 mm

### STANDARD LENGTH

30 yd

27 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

NA

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLORS



Neon  
Orange  
(NEO)



Metallic  
Silver  
(MSL)



Black  
(BLK)



White  
(WHI)

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	105 oz/in width	11.5 N/10 mm
Elongation	10%	10%
Service Temperature Range	32 F to 200 F	0 C to 93 C
Tensile	47 lbs/in width	82.3 N/10 mm
Thickness - Nominal	16.0 mils	0.41 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

